

As part of Northwest Coatings program to communicate health and safety information to our customers, we regularly review and update our MSDS to provide information that is as complete and current as possible. The attached MSDS is the current update for the product that we currently supply to your company. If any hazardous components are present, they will be listed in the MSDS section II Hazardous Components along with the CAS number and the percent present in the compound. Information is also reported in Section II to meet the requirements of SARA Title III – Section 313.

This memo is part of the MSDS and must not be detached from the MSDS. Any copying or redistribution of the MSDS shall include this memo. We suggest you read the enclosed material closely and forward it to the appropriate personnel within your company. If you have any questions about this information, please contact us at 414-762-3330 or Chemtrec at 1-800-424-9300.

NORTHWEST COATINGS

# NORTHWEST COATINGS

## Material Safety Data Sheet

PRODUCT # FT35HG

PAGE 2 OF 3

**NORTHWEST COATINGS**  
7221 SOUTH 10<sup>th</sup> STREET  
OAK CREEK, WI 53154 USA  
PHONE: 414-762-3330

**EMERGENCY PHONE NUMBER:** Chemtrec 800-424-9300  
**PREPARED BY:** S. Lapin  
**PREPARATION DATE:** 3-12-04  
**REVISION DATE:** 05/30/06

### I. PRODUCT IDENTIFICATION

<b>PRODUCT:</b> FT35HG		<b>HMIS CODE</b>
<b>TRADE NAME:</b> HIGH SPEED GLOSS TOPCOAT	<b>HEALTH:</b>	2
<b>CHEMICAL NAME:</b> Mixture	<b>FLAMMABILITY:</b>	1
<b>CHEMICAL FAMILY:</b> UV/EB Curable Product	<b>REACTIVITY:</b>	1
	<b>PERSONAL PROTECTION:</b>	B

### II. HAZARDOUS COMPONENTS

<u>COMPONENT</u>	<u>CAS NUMBER</u>	<u>Weight %</u>	<u>Regulated Under SARA 313</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>
Acrylate Monomers and Oligomers	Trade Secret	Trade Secret	No	Not Established	Not Established

### III. PHYSICAL PROPERTIES

<b>BOILING POINT:</b>	>200°C	<b>SPECIFIC GRAVITY:</b>	>1
<b>APPEARANCE AND ODOR:</b>	Mobil liquid, light amber color, mild acrylate odor.	<b>EVAPORATION RATE (n-Butyl Acetate = 1):</b>	<1
<b>VAPOR PRESSURE (MM HG at 25°C):</b>	<1	<b>VAPOR DENSITY (air=1):</b>	>1
<b>SOLUBILITY IN WATER:</b>	Insoluble		

### IV. REACTIVITY DATA

**STABILITY:** Stable under normal storage and use conditions.

**CONDITIONS TO AVOID:** Storage above 100°F. Direct exposure to sunlight or intense artificial lighting.

**INCOMPATIBILITY (material to avoid):** Polymerization initiators including peroxides, copper, iron, rust and strong bases.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide, Carbon dioxide

**HAZARDOUS POLYMERIZATION:** May occur. Avoid polymerization initiators and storage above 100°F. Maintain air space in containers. Do not blanket containers with nitrogen or other inert gases.

# NORTHWEST COATINGS

## Material Safety Data Sheet

PRODUCT # FT35HG

PAGE 3 OF 3

### V. FIRE & EXPLOSION HAZARD DATA

**FLASH POINT (°F):** >200°F seta flash    **FLAMMABLE LIMITS:** Not established    **LEL:** No data    **UEL:** No data

**EXTINGUISHING MEDIA:** Carbon dioxide or dry chemical for small fires. – Aqueous foam or water fog for large fires.

**SPECIAL FIRE FIGHTING PROCEDURES:** Remove all ignition sources. Wear self-contained breathing apparatus and complete personal protective equipment.

**UNUSUAL FIRE & EXPLOSION HAZARDS:** High temperature may cause rapid polymerization which can result in the violent ruptures of storage containers.

### VI. HEALTH HAZARD DATA

**A. LISTED CARCINOGENICITY:**    **IARC -** No    **NTP -** No    **OSHA -** No

**B. EFFECTS OF OVEREXPOSURE**    Effects may be delayed. May result in sensitization.

**EYE:**    Eye irritant, Direct contact may cause eye injury.

**SKIN:**    Skin irritant, Direct contact may cause skin injury (reddening or burn).

**INHALATION:**    May irritate nose, throat, and lungs. Only slightly toxic by inhalation.

**INGESTION:**    Only slightly toxic by ingestion.

**KNOWN EFFECTS ON OTHER ILLNESS:**    None known.

**C. EMERGENCY AND FIRST AID PROCEDURES**

**EYE:**    Flush eyes with water, remove contact lenses, get medical attention.

**SKIN:**    Wipe off excess, immediately wash with soap and water.

**INHALATION:**    Leave exposure area and seek fresh air.

**INGESTION:**    Seek medical attention.

**D. PROTECTIVE EQUIPMENT**

**EYE:**    Chemical safety goggles.

**SKIN:**    Impervious gloves such as Neoprene, nitrile, or latex.

**VENTILATION:**    Local ventilation of work area recommended.

**RESPIRATORY PROTECTION:**    None required under most application conditions. If local ventilation is not adequate, use an organic vapor respirator under conditions that produce increased airborne levels such as misting or elevated temperatures.

**OTHER PROTECTIVE EQUIPMENT:**    Where contact may occur use face shield, impervious body covering and boots.

### VII. PRECAUTIONS FOR SAFE HANDLING AND STORAGE

**A. STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK**

Provide adequate ventilation. Absorb spill with sawdust, claw, etc. Use eye and skin protection. Sweep up and place in waste disposal containers. Wash affected area with detergent and water.

**B. HANDLING AND STORAGE:**

Store in a cool, dry location, away from heat and sunlight. Store below 100°F.

### VIII. OTHER DISPOSAL INFORMATION

Generally considered non-hazardous for disposal purposes. Dispose in accordance with local, state, and federal regulation. Incineration recommended.