



Cycletime Tips - General

Volume 40: Commonly Used Conversion Factors for Plastic Materials

This is our most current Conversion Table. We think this information will be very useful to our Customers. We will update this information from time to time.

To Convert	MultiplyBy	To Obtain	To Convert	MultiplyBy	To Obtain
			kg/cm ²	0.1	MPa
ϕ/lb	0.036(sp grav)	ϕ/in ³	kg/cm ²	14.22	psi
°C	1.8(°C) + 32	°F	kg-cm/cm	0.18	ft-lbs/in
°F	0.56(°F - 32)	°C	kg-cm/cm	9.81	J/m
ft-lbs	1.36	J	kg-cm/cm ²	0.47	ft-lbs/in ²
ft-lbs	13.83	kg-cm	kg/m ³	0.001	g/cm ³
ft-lbs/in	3.23 ISO	ft-lbs/in ²	kJ/m ²	10.2 ASTM	J/m
ft-lbs/in	53.39	J/m		kJ/m ²	0.19 ASTM
ft-lbs/in	5.44	kg-cm/cm	kJ/m ²		0.48
ft-lbs/in	5.24 ASTM	kJ/m ²	kJ/m ²	8 ISO	J/m
ft-lbs/in	6.68 ISO	kJ/m ²	kJ/m ²	0.15 ISO	ft-lbs/in
ft-lbs/in ²	0.31 ISO	ft-lbs/in	kN/m	5.7	lbs/in
ft-lbs/in ²	2.12	kg-cm/cm ²	lbs/in	0.18	kg/cm
ft-lbs/in ²	2.07 ISO	kJ/m ²	lbs/in	0.175	kN/m
g/cm ³	1,000	kg/m ³	lbs/in	175	N/m
in/in/°F	1.8	mm/mm/°C	microns	0.000039	in
in/min	25.4	mm/min	microns	0.039	thousandths
in-lbs	0.11	J	miles/hr	0.45	m/sec
in-lbs	1.15	kg-cm	mm/min	0.039	in/min
J	0.74	ft-lbs	mm/mm/°C	0.56	in/in/°F
J	8.85	in-lbs	MPa	10.2	kg/cm ²
J	10.2	kg-cm	MPa	145	psi
J/m	0.019	ft-lbs/in	m/sec	2.24	miles/hr
J/m	0.10 ASTM	kJ/m ²			

J/m	0.12 ISO	kJ/m ²	N/m	0.0057	lbs/in
J/m	0.1	kg-cm/cm	N/mm ²	145	psi
kg-cm	0.07	ft-lbs	psi	0.0069	N/mm ²
kg-cm	0.87	in-lbs	psi	0.0069	MPa
kg-cm	0.1	J	psi	0.07	kg/cm ²
kg/cm	5.6	lbs/in			

If "ASTM" is noted, the indicated conversions apply to an ASTM notched Izod test specimen. If "ISO" is noted, the indicated conversions apply to an ISO notched Izod specimen.

Notice: All precautionary labels and notices should be fully read and understood by all supervisors, personnel and employees before using any product. For additional safety and health information, contact Ashland Distribution Company. Purchaser has the responsibility for determining any applicability of a compliance with federal, state and local laws and/or regulations involving use, particularly in making consumer products.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warrant, negligence, or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.